

**PRODUCT SELECTION MATRIX**

# MINI-STRIKER® SERIES



		MINI-STRIKER Vehicle Mount		MINI-STRIKER Portable	
		MSTR-V		MSTR-P	
SPECIFICATIONS	Performance (standard NFPA Conditions)	Flow @ 25 PSI (1.7 BAR)			68 GPM (257 lpm)
		Flow @ 50 PSI (3.4 BAR)			42 GPM (159 lpm)
		Flow @ 75 PSI (5.2 BAR)			12 GPM (45 lpm)
		Maximum Pressure			85 PSI (5.9 BAR)
		Maximum Flow			80 GPM (303 lpm)
	Pump Type	High Pressure - Medium Flow			1-Stage Centrifugal Pump
	Pump Standard Connections	Intake			1-1/2" Male NPSH
		Discharge			1-1/2" Male NPSH
	Engine Type	Air Cooled Gasoline			Honda GXH50
	Engine Max Power	[Torque]			2.1 HP (1.6 kW) @ 7,000 RPM [2.0 lb-ft (2.7 Nm) @ 4,500 RPM]
Fuel Tank	Integral .2 US gal (0.77 L)			0.2 US Gallon (0.77 L)	
Frame		Industrial Isolators		Poly base with rubber mount	
Dry Weight*		19 lbs (8.6 kg)		20 lbs (9 kg)	

\* Approximated and varies based off option selections